



Filter Assemblies

Model 207-12259-1 (60 Mesh)

Model 207-12259-2 (100 Mesh)

CAUTION
Maximum working pressure of this assembly is 1800 psi (124 bar).

CAUTION
Before performing any maintenance on this assembly:
Make sure to relieve all pressure from system.

ITEM	PART#	DESCRIPTION	QUANTITY	
			207-12259-1	207-12259-2
1	237-847	PULSATION CHAMBER	1	1
2	207-12282	ADAPTER WITH O-RING	1	1
2a	237-848	O-RING	REF	REF
3	72-999	DM NIPPLE	1	1
4	20-4283	SWIVEL ADAPTER	1	1
5	237-280	STREET TEE	1	1
6	20-2097	PIPE PLUG	1	1
7	20-2605-1	PIPE PLUG	2	2
8	207-11689	FILTER HEAD	1	1
9	237-696	O-RING	1	1
10	207-11691	FILTER SUPPORT	1	1
11	207-11693	SCREEN - 60 MESH	1	-
11	207-11694	SCREEN - 100 MESH	-	1
12	207-11697	SPRING	1	1
13	207-11688	FILTER BOWL	1	1
14	72-13030	HP BALL VALVE	1	1

NOTE
Pulsation chamber to be used in a vertical position as shown. Be sure to check the pulsation chamber regularly for material build up.

REPLACEMENT PARTS

This filter assembly is designed to use authorized parts only. When using this filter assembly with parts that do not comply with the minimum specifications and safety devices of Binks, the user assumes all risks and liabilities.



PROP 65 WARNING
WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

77-2807R-1 Revisions: Trademark updates, added Prop 65 warning, updated contact information.

WARRANTY

This product is covered by Binks' 1 Year Limited Warranty.

Binks Sales and Service: www.binks.com



U.S.A./Canada Customer Service
195 Internationale Blvd.
Glendale Heights, IL 60139
630-237-5000

Toll Free Customer Service
and Technical Support
800-992-4657

Toll Free Fax
888-246-5732

